

# Nu-Coat

## Floor Sealer



### Applications:

#### Preparation:

Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry.

#### Application:

Using a clean mop or sprayer, apply 2-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 30-60 minutes or more depending on humidity condition.

### Benefits:

- Ideal as a base coat for floor finishes
- The solids fill and seal pores as they harden
- Provides a smoother floor surface
- Excellent slip resistance
- Detergent resistant
- High durability for long-lasting protection
- Protects both resilient and non-resilient floors

### Codes:

- **Product Code:** 55046 (20 L)
- **UPC:** 0 56069 55046 8 (20 L)

### Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.4 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing
Coverage	170 m <sup>2</sup> (1830 ft <sup>2</sup> ) to 280 m <sup>2</sup> (3014 ft <sup>2</sup> ) (5 L)
Number of Coats	2 - 3
Drying Time	30 - 60 minutes
Solid Content	12%
COF	0.7
Shelf Life	Up to 3 years after manufacturing



### Available Format:



20 L

### Packaging:

**Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)  
48 lbs (22 kg)