

# Accolade

## Floor Sealer & Finish

### Applications:

**Preparation:** Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry.

**Application:** Using a clean mop or sprayer, apply 2-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 30-60 minutes or more depending on humidity condition.

### Benefits:

- Ideal as a base coat for floor finishes
- The solids fill and seal pores as they harden
- Provides a smoother floor surface
- Excellent slip resistance
- Detergent resistant
- High durability for long-lasting protection
- Protects both resilient and non-resilient floors

### Codes:

**Product Code:** **53784** (5 L)  
**53785** (20 L)

**UPC:** **0 56069 53784 1** (5 L)  
**0 56069 53785 8** (20 L)

### Available Format:



5 L



20 L

### Packaging:

**Bottle:** 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)  
12.25 lbs (5.56 kg)

**Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)  
48 lbs (22 kg)

**Box (5 L):** 12.4" x 12.4" x 13"  
49 lbs (22.23 kg)  
4 per case

## Specifications

<b>Colour</b>	White
<b>DIN</b>	No
<b>Odour</b>	Acrylic
<b>pH</b>	8.4 - 8.8
<b>Viscosity</b>	Not determined
<b>Solvent</b>	No
<b>Phosphates</b>	No
<b>WHMIS</b>	Yes
<b>ECOLOGO</b>	No
<b>Food Safe</b>	No
<b>Kosher</b>	Yes
<b>Shelf Life</b>	Up to 3 years after manufacturing
<b>Coverage</b>	170 m <sup>2</sup> (1830 ft <sup>2</sup> ) to 280 m <sup>2</sup> (3014 ft <sup>2</sup> ) (5 L)
<b>Number of Coats</b>	2 - 3
<b>Drying Time</b>	30 - 60 minutes
<b>Solid Content</b>	20%
<b>COF</b>	0.7
<b>Shelf Life</b>	Up to 3 years after manufacturing
<b># of Cases per pallet</b>	36 (5 L) / 36 pails (20 L)

